

Kincora

PRODUCT INFORMATION SHEET

www.kincora.net

Tel: 01621 828882

This Information Sheet is for products KIN GREASE

HEALTH & SAFETY DATA:

Suggestions and recommendations covering the use of the products based on past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of products within manufacturing tolerances.

PRODUCT: MAINTENANCE AEROSOLS - WHITE GREASE

1. IDENTIFICATION OF THE PREPARATION AND THE COMPANY:

CHEMICAL NAME: White Grease

2. COMPOSITION/INFORMATION ON INGREDIENTS:

INGREDIENT NAME	CAS No.	CONTENTS	HEALTH (Class)	RISK (R No.)
Naptha (Petroleum)				
Hydrotreated Light	64742-49-0	30-60%	F, Xn, N	11, 38, 51/53, 65,67
Hydrocarbon Propellant	68476-85-7	10-30%	Fx	12

COMPOSITION COMMENTS: Aerosol propelled by liquefied petroleum gas.

3. HAZARDS IDENTIFICATION:

Extremely flammable

Irritating to skin

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness & dizziness

4. FIRST AID MEASURES:

EYES: Promptly wash eyes with lots of water while lifting the eyelids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

SKIN: Wash the skin immediately with soap and water. Get medical attention if irritation persists.

INHALATION: If inhalation of vapours causes irritation or drowsiness, remove to fresh air.

5. FIRE FIGHTING MEASURES:

EXTINGUISHING MEDIA: Fire can be extinguished using powder, foam or CO2.

SPECIAL FIRE FIGHTING PROCEDURE: Use water to keep fire-exposed containers cool and disperse vapours. Breathing apparatus should be worn if exposure to fumes is likely.

UNUSUAL FIRE \$ EXPLOSION HAZARDS: Possible risk of can rupture when exposed to fire/high temps. Contents of aerosol will add to fuelling of fire. Solvent vapours may form explosive mixtures with air.

6. ACCIDENTAL RELEASE MEASURES:

PROCEDURES FOR LEAKS & SPILLAGE'S

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb materials from ruptured or leaking cans onto an inert material. Transfer to suitable container for subsequent disposal.

7. HANDLING AND STORAGE:

USAGE PRECAUTIONS: Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. **CAUTION:** Pressurised container. Do not expose to temperatures exceeding 50 deg C. Do not puncture or incinerate even when empty. Do not spray onto naked flame or any incandescent material.

STORAGE PRECAUTIONS: Store in cool; dry place away from all sources of heat including direct sunlight

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

INGREDIENT	CAS No.	STD	LT EXP (8hrs)	ST EXP (10 min)
Naptha (petroleum) Hydrotreated Light	64742-49-0		400ppm	

INGREDIENT COMMENTS: OES - Occupational Exposure Standard

PROTECTIVE EQUIPMENT:

PROTECTIVE GLOVES: Chemical resistant gloves required for prolonged or repeated contact.

EYE PROTECTION: Safety goggles/glasses are advised if there is a risk of eye contact.

9. PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE: Aerosol

10. STABILITY AND REACTIVITY:

MATERIALS TO AVOID: Strong oxidising agents.

CONDITIONS TO AVOID: Avoid heat, flames and other sources of ignition.

HAZARDOUS DECOMPOSITION PRODUCTS: Fire or high temp. create: Carbon Dioxide (CO₂), Carbon Monoxide (CO).

11. TOXICOLOGICAL INFORMATION:

HEALTH WARNINGS:

EYE CONTACT: May cause irritation to eyes.

SKIN CONTACT: Irritating to skin. Repeated exposure may cause skin dryness or cracking.

INHALATION: High concentrations of vapour may cause dizziness, nausea and headaches.

INGESTION: May cause irritation to mouth, respiratory tract and intestinal system.

12. ECOLOGICAL INFORMATION:

ACUTE FISH TOXICITY: Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS:

Do not puncture or incinerate even when empty. Dispose of in accordance with local authority requirements.

14. TRANSPORT INFORMATION:

LABEL FOR CONVEYANCE:

ROAD

UN No: 1950

ADR CLASS: Class 2: Gases, Compressed, liquefied or dissolved under pressure.

SEA

UN SEA: 1950

AIR

UN AIR: 1950

15. REGULATORY INFORMATION:

LABEL FOR SUPPLY:

RISK PHRASES:	R-12	Extremely flammable
	R-36	Irritating to skin
	R-51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	R-67	Vapours may cause drowsiness & dizziness
SAFETY PHRASES:	S-2	Keep out of reach of children.
	S-9	Keep container in a well ventilated place.
	S-16	Keep away from sources of ignition - No smoking
	S-23	Do not breathe gas/vapour/spray/fumes
	S-24	Avoid contact with skin
	S-29/35	Do not enter into drains, dispose of this material in a safe way.
	S-35	This material and its container must be disposed of in a safe way.
S-51	Use only in well ventilated areas	

16. OTHER INFORMATION:

SDS NO:	A2614	
R-PHRASES (Full Text):	R-11	Highly Flammable
	R-12	Extremely flammable
	R-38	Irritating to skin
	R-51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	R-65	Harmful: May cause lung damage if swallowed
	R-66	Repeated exposure may cause skin dryness or cracking.

DISCLAIMER:

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.